


- NOTES:
- 1. TOLERANCE BLOCK DOES NOT APPLY.
 - 2. UNLESS OTHERWISE NOTED, THE GENERAL TOLERANCE IS $\pm 0.20\text{mm}$.

APPLICABLE PN		
Class	Product #	Description
Specialty LEDs (UV)	LZ1-10UA00	Violet (385nm, 395nm, 405nm)
	LZ1-10U600	Ultraviolet (365nm)
	LZ1-10UV00	Ultraviolet (365nm)

Pin Out				
Ch.	MCPCB Pad	Emitter Pad	Function	String
1	1	-, -	Cathodes	1x1
	2			
	3			
	4	+, +	Anodes	
	5			
	6			

<div></div> <div>Third Angle Projection</div> <div>DIMENSIONS ARE IN MILLIMETERS</div> <div>TOLERANCES:</div> <div><div>.X ± 0.5</div><div>.XX ± 0.25</div><div>.XXX ± 0.10</div><div>Angle ± 1°</div></div> <div>MATERIAL:</div> <div>N/A</div> <div>FINISH:</div> <div>N/A</div>		NAME	DATE	<div>LED Engin, Inc.</div> <div>TITLE: LZ1, 1 CHANNEL, MCPCB with LZ1 (UV) Emitter (SOLID VIEWS)</div> <div><div>SIZE B</div><div>DWG. NO. LZ1-10Ux00-P3</div><div>REV A3</div></div>		
	DRAWN	DAA	04/30/14			
	CHECKED					
	ENG APPR.					
	MFG APPR.			THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF LED ENGIN, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF LED ENGIN, INC. IS PROHIBITED.		
	Q.A.					
PROPRIETARY AND CONFIDENTIAL						
FILE NAME: LZ1-10Ux00-P3_LZ1(customer)_RevA3			SCALE: 4:1		SHEET 1 OF 1	